#### Hill-Roma

### Surgical Stretcher



## Hill-Rom<sub>®</sub> Surgical Stretcher

### At a glance

Hill-Rom stretcher key features:

- 700 lb. weight capacity
- Low height for safer stretcher ingress and egress
- Articulating head section for maximum flexibility
- Surgical rail for easy attachment of gas, extenders, and hand tables
- **Integrated IV pole transport device** helps maneuver the stretcher and a portable IV with ease
- Next generation Steering Plus<sub>™</sub> system for crisp cornering and control
- **Dual-locking, four-wheel brakes** for a strong, stable platform
- · Power washable
- Three year parts warranty and lifetime frame weld warranty

Hill-Rom's flexible surgical stretcher (P8010) is ideal for any surgical setting, including outpatient, OR or freestanding surgery centers. Built to last year after year, this stretcher offers outstanding mobility, functionality and quality.

Mobility. Our next generation Steering Plus™ system allows crisp cornering and control, and dual-locking, four-wheel brakes for a strong, stable platform. The integrated IV pole transport device helps maneuver the stretcher and IV pole stands with ease.

**Functionality.** The articulating head section and wrist rests are designed to suit a variety of surgeon preferences, regardless of the setting or type. A surgical rail allows easy attachment of gas delivery and drape support devices, PACU extenders and armboards, and surgical hand tables.

**Quality.** Our reinforced frames are made of heavy-gauge, automotive grade steel for long-lasting quality – and a 700 lb. weight capacity to handle higher patient weights. Nickel-plated push handles, IV poles, siderails and other components offer superior rust resistance, even in harsh environments.



<sup>\*</sup> Optional feature

#### Hill-Rom<sub>®</sub>

## **Surgical Stretcher**

Features	Standard Features	Optional Features
700 lb. weight capacity	•	
Integrated IV pole transport device		•
Brake/Steer pedals — head and foot	•	
Brake/Steer pedals — all four sides		•
Next generation Steering Plus™ system	•	
Ergonomic push handles (foot only)		•
Permanent IV pole — 3 stage (foot only)		•
26-inch width	•	
Manual knee gatch		•
Foot end hi/lo hydraulic pedals		•
Siderail system	Tuck-away	
Slow descent hydraulics	•	
4-inch high density foam mattress with fire barrier		•
Bumper colors — choice of neutral, blue, red, teal or purple	Choice	



IV Pole Transport Device



PACU Armboard Extender



Four-sided Brake/Steer



Articulating Head Section

# **Technical Specifications**

Maximum weight limit	700 lbs. (317.5 kg)
Low position — floor to top of surface	-
High Position — floor to top of surface	33.25" (84.5 cm)
Overall length	92" (233.7 cm)
Overall width (siderails up)	32" (81.3 cm)
Overall width (siderails stored)	26" (66 cm)
Siderail length	47" (119.4 cm)
Siderail height above mattress/surface	14" (36.8 cm)
Mattress size	26" (66 cm) x 78" (198.1 cm)
Maximum head elevation	70°
Maximum Trend/Reverse Trend	18°
Floor to base clearance	3.5" (8.9 cm)
Caster size	8" (20.3 cm)

## **Accessories**

- IV transporter
- Patient tray
- Utility tray
- Oxygen tank holder
- Liquid oxygen tank holder
- Infusion support system
- Siderail covers
- Armboard
- Detachable footboard
- Lateral x-ray cassette holder
- Chart holder

- · Accessory IV pole
- Ankle stirrups
- Transport straps
- Foot extender
- Paper roll dispenser
- Gas delivery/drape support
- · Head restraint strap
- Temporal wrist rest
- Superior wrist rest
- Integrated removable armboard with pads

Hill-Rom reserves the right to make changes without notice in design, specifications and models. The only warranty Hill-Rom makes is the express written warranty extended on the sale or rental of its products.

© 2008 Hill-Rom Services, Inc. ALL RIGHTS RESERVED.

